

MASTER 500

humidity for productivity...

Master 500 is designed for controlled atmosphere (CA), ultra low oxygen (ULO), traditional cold storage rooms and the places where you need humidity. Wide use range is benefit of Master 500.

FEATURES:

- Design of Master 500 is avoiding mixing of external air with internal air.
- Installation of unit can be done outside of coldroom. On period of maintenance you don't need to service out the cold room.
- Maintenance is every 5000 working hour with low cost.
- By using standart water piping equipments you can mount inlet and outlet of mist air.

SPECIFICATIONS:

Water Rate: 5000ml/h
Power Supply: 220-230Vac / 50Hz
Power Consumption: 305W
Air Flow: 170m³/h
Ambient Condition: 1° - 40°
Life Time of Oscillators: 5000h
Air Speed On Output: 14m/s
Water Supply Connection: 1/2"
Air In Connection: 63mm 2"
Mist Out Connection: 63mm 2"
Weight With Water: 24kg



www.nebulamist.com



MASTER 500	
Water Rate	5000ml/h
Power Supply	220-230Vac
Power Consumption	305W
Air Flow	170m ³ /h
Ambient Condition	1° - 40°
Life Time of Oscillators	5000h
Air Speed On Output	14m/s
Water Supply Connection	1/2"
Air In Connection	63mm 2"
Mist Out Connection	63mm 2"
Weight With Water	24kg
Model Number	MS500
www.nebulamist.com	